

When it must be very quiet




SKF BeQuiet+ test rig.
Image with kind permission
of SKF.

Examples of application

- Ball bearings in electric drives of motor vehicles
- High-speed plain and roller bearings
- High-speed spindle bearings, e. g. in machine tools and textile machines
- Low-noise roller bearings in household appliances
- Toothed gears in small gears
- Worm gears

Properties

- Excellent performance in high-speed spindle bearing test rig WS 22 (speed factor in hybrid bearing: 2.25 million)
- Low noise level
- For high and low temperatures
- High load-carrying capacity
- Excellent consistency-temperature-behavior
- Well suitable for shock loads and vibrations
- Good adhesion on metallic surfaces



rpm limit
 $n \times d_m$



in the SKF
BeQuiet test*



base oil viscosity
at 40 °C



NLGI class

» Berutemp PE 2-10 HS impresses with its unique combination of high-speed properties and excellent noise class despite high base oil viscosity. «

Low noise high-speed grease

Berutemp PE 2-10 HS is a new low noise high-speed lubricating grease of noise class GN4, which has already been successfully used in extremely high-speed hybrid bearings at speed characteristics of $n \times d_m = 2.25$ million. At the same time, with a base oil viscosity of 100 mm²/s at 40 °C, it is also suitable for slower speeds, covering a uniquely wide range of operating conditions.

Due to its high load carrying capacity and very good dynamic resistance, Berutemp PE 2-10 HS can be used, for example, in rolling bearings in the drive trains of electric vehicles, in high-speed spindle bearings in machine tools and textile machines, or in low-noise rolling bearings in household appliances.

FAG WS 22 spindle bearing test (hybrid bearings)

— Bearing 1
— Mean value
— Bearing 2

$n \times d_m = 2.25$ million
53,000 min⁻¹ x 42.5 mm = 2,250,000 mm/min
Temperature difference:
Bearing temperature to room temperature

*Best possible noise class: GN4

